



Liberty Marking Systems, Inc.
7265 Edington Dr.
Cincinnati, OH 45249
513-530-9270 FAX 513-530-9272

Product Data Sheet

209 Silver (Matte) 2 mil Polyester

Liberty 209 is a topcoated (matte finish), thermal transfer printable (resin) silver polyester with a highly aggressive permanent pressure sensitive acrylic adhesive and backed with a kraft release liner.

Service Temperature Range	-40° F to 302° F (-40° C to 150° C)
Minimum Application Temperature	32° F (0 C)
Expected Exterior Life	Two years
Storage Stability	Two years stored at 70° F (21° C) and 50% RH

PHYSICAL CHARACTERISTICS:

Thickness	Film	2.0 mils +/- 10%
	Adhesive	.9-1.0 mils +/- 0.1
	Liner	3.1 mils +/- 10%
Dimensional Stability	No shrinkage observed on aluminum panel at 160° F (70° C) for 24 hours.	

TOP COATING:

The topcoating is suitable for thermal transfer printing using resin based thermal transfer ribbon.

Product Performance and Suitability

All of the descriptive information and recommendations for the use of Liberty Marking Systems products are to be used only as a guide. The furnishing of such information and recommendations shall in no event constitute a warranty of any kind by Liberty Marking Systems. All purchasers of Liberty Marking Systems products shall independently determine the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Liberty Marking Systems is authorized to give any warranty, guarantee, or to make any representation in addition or contrary to the above.